

EXTENDED RATINGS

MULTI18HP230V1CO

HEATING PERFORMANCE

DB WB		Indoor Ambient Temperature															
		70°F (21°C) 59°F (15°C)				75°F (24°C) 63°F (17°C)				80°F (27°C) 67°F (19°C)							
	DB	TC (BtuH)	SC (BtuH)	Input Power (watts)	COP(W /W)	TC (BtuH)	SC (BtuH)	Input Power (watts)	COP(W /W)	TC (BtuH)	SC (BtuH)	Input Power (watts)	COP(W /W)				
Outdoor Ambient Temperature (DB)	-5°F (-21°C)	10,865	10,865	1,840	1.73	10,656	10,656	1,880	1.66	10,325	10,325	1,920	1.58				
	0°F (-18°C)	11,121	11,121	1,800	1.81	10,800	10,800	1,840	1.72	10,598	10,598	1,880	1.65				
	5°F (-15°C)	11,428	11,428	1,751	1.91	11,099	11,099	1,791	1.82	10,891	10,891	1,831	1.74				
	7°F (-14°C)	11,736	11,736	1,722	2.00	11,397	11,397	1,762	1.90	11,184	11,184	1,802	1.82				
	17°F (-8°C)	12,597	12,597	1,663	2.22	12,229	12,229	1,703	2.11	11,997	11,997	1,743	2.02				
	28°F (-2°C)	14,230	14,230	1,601	2.60	13,856	13,856	1,641	2.47	13,458	13,458	1,681	2.35				
	38°F (3°C)	17,693	17,693	1,593	3.26	17,319	17,319	1,633	3.11	16,927	16,927	1,673	2.97				
	47°F (8°C)	19,997	19,997	1,590	3.69	19,392	19,392	1,630	3.49	19,006	19,006	1,670	3.34				
	57°F (14°C)	20,657	20,657	1,519	3.99	20,033	20,033	1,559	3.77	19,635	19,635	1,599	3.60				
	68°F (20°C)	21,490	21,490	1,495	4.21	20,840	20,840	1,535	3.98	20,430	20,430	1,575	3.80				
	77°F (25°C)	21,990	21,990	1,461	4.41	21,330	21,330	1,501	4.16	20,900	20,900	1,541	3.97				

LEGEND

DB --- Dry Bulb
WB --- Wet Bulb
TC --- Total Net Cooling Capacity (BtuH)
SC --- Sensible Capacity (BtuH)
Input Power---(Watts)

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All rights reserved.