

# SAFE- - SWITCH

#### CONDENSATE OVERFLOW PROTECTION



**Top Quality**. **Every Switch** is run tested

to ensure quality.

Durable.

Thicker stem.

Secure. Embedded magnets • won't fall out.

**Stronger.** Extended magnet surface area. Smoother operation.

# The most reliable

# switch.



# SAFE-T-SWITCH® US Patent No. 6,442,955

### Fully adjustable activation level reduces nuisance

shutdowns. Taller body and longer float shaft combine to allow greater float adjustment.

### Patented Reliability.

15+years of proven condensate overflow protection against water damage.\* Millions in service worldwide.

## Simple Installation.

Switch need not be installed level or plumb. Fits standard pipe sizes. Adaptors included.

\*In 2013, the average home insurance claim was \$8,787, with roughly 20% water damage related claims.

# SS1 Float Switch

Code	Description	Qty.
97632	Model SS1	24
97630	Contractor Pack	50

#### FEATURES

LISTED

IND. CONT

EQ. 75MF UL 508

Condensate overflow switch

- Magnetic reed switch
- Install vertically or horizontally Connect to either red or
- yellow wire • NEW! Includes directional cleanout tool to provide cleanout access.
- POP Blister packaged

#### For primary drains or auxiliary drain outlets

**APPLICATION** • Detects clogged A/C condensate drains and shuts off the system to prevent water damage to floors, walls and ceilings • Can be installed horizontally or vertically, inline or on the primary pan's auxiliary drain outlet by using the included 3/4" adapter, bushing and cap • Can be installed on a sloping line and does not need to be level or plumb US Patent No. 6,442,955

SAFE-T-SWITCH

Can be installed in a horizontal or vertical position

# SS2 Float Switch

Code	Description	Qty.
97637	Model SS2	24
97635	Contractor Pack	50

Üι LISTED IND. CONT EQ. 75MF UI 508

#### FEATURES Condensate overflow switch

 Magnetic reed switch • Connect to either red or vellow wire

POP Blister packaged

### For primary drain pan auxiliary outlet

**APPLICATION** • Detects clogged A/C condensate drains and shuts off the system • Using the 3/4" adapter the SS2 can be installed on the auxiliary outlet of the primary drain pan • Easy access to the switch and the primary drain line for service

US Patent No. 6,442,955

A plenum rated model is available - SS2AP

# SS3 Float Switch

Code	Description	Qty.
97647	Model SS3	24
97645	Contractor Pack	50

FEATURES Condensate overflow switch LISTED Magnetic reed switch IND. CONT Connect to either red or yellow wire UL 508 POP Blister packaged

## For primary and auxiliary drain pans

**APPLICATION** • Detects clogged A/C condensate drains and shuts off the system • Steel mounting bracket clips firmly over the edge of most drain pans • Slim profile can be installed on primary or auxiliary drain pans.

US Patent No. 6,698,215





٧L

EQ. 75MF

2601 Spenwick Drive, Houston, TX 77055 713-263-8001 800-231-3345 rectorseal.com

RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice ©2018 RectorSeal. All rights reserved. R50318 10-18