

Alpine Home Air Products

Address:1509 Coral Ridge Rd Suite A, Shepherdsville, KY 40165 Phone: (800) 865-5931 https://www.alpinehomeair.com/ Date:2023.04.12

Equipment control cable

Application

Internal wiring or external inter-connection of electronic equipment (such as desk-type calculators, ,temperature control equipment or X-ray equipment)

Standard UL 20626 Rated Voltage					
150V Construction					
Conductor	Solid copper				
Insulation	PVC		4		
Sheath	Sunlight-resistant PVC			4	
	Conductor	Insulation	Sheath	Overall	Approx.
Cross Section of Conduc	tor C + + D' +	thickness	thickness	Diameter	Weight

	Conductor		Insulation	Sheath	Overall	Approx.
Cross Section of Conductor	Construction	Diameter	thickness	thickness	Diameter	Weight
	(No. / in)	(in)	(in)	(in)	(in)	(lb / FT)
8*18AWG	1*0.04	0.04	0.01	0.04	0.3	0.08

Feature:

Rated Temperature: 194°F Rated Voltage:150V Spark Voltage: 3KV. Dielectric Strength: 2000Vac for 60 seconds without breakdown. Flammability Grade: FT1

Insulation Color:

8 cores: Black/Red/White/Green/Brown/Blue/Orange/Yellow.

Sheath Color:

8 cores: Brown

Cut length and quantity

Wire length (ft)	50
Cable type	8*18
Number of packages	563
Quantity	28150

Packing

Make rolls according to specified length on the standard wooden pallet