

SUBMITTAL DATA SHEET



| | |
|---------------------|--|
| BM09MCC | Cassette Heat Pump Air Handlers |
| Location: _____ | Approval: _____ |
| Engineer: _____ | Date: _____ |
| Submitted to: _____ | Construction: _____ |
| Submitted by: _____ | Unit #: _____ |
| Reference: _____ | Drawing #: _____ |

Indoor unit code 453076222

Indoor unit model BM09MCC

Certified UL US



| INDOOR UNIT DATA | | |
|--|--|----------------|
| Power supply | | |
| Normal Operational Voltage (V, Ph, Hz) | | 208/230, 1, 60 |
| Voltage Range (V) | | 187-253 |
| Indoor fan motor | | |
| Type | | Cross-Flow |
| Model | | ZKFP-46-8-1 |
| Qty | | 1 |
| Input (W) | | 45.0 |
| RLA (A) | | - |
| LRA (A) | | - |
| Winding Resistance (Ω) | | - |
| Capacitor (uF) | | - |
| Speed(Hi/Mi/Lo) (r/min) | | 600/520/460 |

| INDOOR UNIT DATA | | |
|---------------------------------------|------|----------------------|
| Air flow & Noise level | | |
| Indoor air flow (Hi/Med/Lo) (CFM) | | 352.94/305.88/270.59 |
| Indoor noise level (Hi/Med/L) [dB(A)] | | 39.5/36/32.5 |
| Dehumidification (Pint/H) | | --- |
| Indoor unit | | |
| Dimension (WxDxH) (inch) | | 22.44x22.44x10.24 |
| | (mm) | 570x570x260 |
| Packing(WxDxH) (inch) | | 26.06x26.06x12.48 |
| | (mm) | 662x662x317 |
| Net/Gross weight (lbs.) | | 31.97/38.14 |
| | (kg) | 14.5/17.3 |
| Liquid side/ Gas side (inch) | | 1/4" / 3/8" |
| | (mm) | 6.35/9.52 |
| Application area (sq.ft) | | 129.17~193.75 |
| | (m2) | 12~18 |

