

SUBMITTAL DATA SHEET



BM12MCC	Cassette Heat Pump Air Handlers
Location: _____	Approval: _____
Engineer: _____	Date: _____
Submitted to: _____	Construction: _____
Submitted by: _____	Unit #: _____
Reference: _____	Drawing #: _____

Indoor unit code 453076065

Indoor unit model BM12MCC

Certified UL US



INDOOR UNIT DATA		
Power supply		
Normal Operational Voltage (V, Ph, Hz)		208/230, 1, 60
Voltage Range (V)		187-253
Indoor fan motor		
Type		Cross-Flow
Model		ZKFP-46-8-1
Qty		1
Input (W)		45.0
RLA (A)		-
LRA (A)		-
Winding Resistance (Ω)		-
Capacitor (uF)		-
Speed(Hi/Mi/Lo) (r/min)		680/580/500

INDOOR UNIT DATA		
Air flow & Noise level		
Indoor air flow (Hi/Med/Lo) (CFM)		379/309/261
Indoor noise level (Hi/Med/L) [dB(A)]		40.5/35.5/31.5
Dehumidification (Pint/H)		---
Indoor unit		
Dimension (WxDxH) (inch)		22.44x22.44x10.24
	(mm)	570x570x260
Packing(WxDxH) (inch)		26.06x26.06x12.48
	(mm)	662x662x317
Net/Gross weight (lbs.)		35.27/41.01
	(kg)	16/18.6
Liquid side/ Gas side (inch)		1/4" / 1/2"
	(mm)	6.35/12.7
Application area (sq.ft)		172.22~247.57
	(m2)	16~23

