

SUBMITTAL DATA SHEET



BLUERIDGE

BM18MCC

Cassette Heat Pump Air Handlers

Location: _____

Engineer: _____

Submitted to: _____

Submitted by: _____

Reference: _____

Approval: _____

Date: _____

Construction: _____

Unit #: _____

Drawing #: _____

Indoor unit code

453076223

Indoor unit model

BM18MCC

Certified

UL





INDOOR UNIT DATA			INDOOR UNIT DATA		
Power supply			Air flow & Noise level		
Normal Operational Voltage	(V, Ph, Hz)	208/230, 1, 60	Indoor air flow (Hi/Med/Lo)	(CFM)	562.35/485.29/438.82
Voltage Range	(V)	187-253	Indoor noise level (Hi/Med/L)	[dB(A)]	43.5/38.5/35.5
Indoor fan motor			Dehumidification	(Pint/H)	---
Type		Cross-Flow	Indoor unit		
Model		ZKFP-46-8-1	Dimension (WxDxH)	(inch)	22.44x22.44x10.24
Qty		1		(mm)	570x570x260
Input	(W)	45.0	Packing(WxDxH)	(inch)	26.06x26.06x12.48
RLA	(A)	-		(mm)	662x662x317
LRA	(A)	-	Net/Gross weight	(lbs.)	35.71/46.96
Winding Resistance	(Ω)	-		(kg)	16.2/21.3
Capacitor	(uF)	-	Liquid side/ Gas side		
Speed(Hi/Mi/Lo)	(r/min)	730/630/570		(inch)	1/4" / 1/2"
				(mm)	6.35/12.7
			Application area		
				(sq.ft)	226.04 ~ 333.68
				(m2)	21 ~ 31

