

Heating

| Outdoor | 68F DB (20C) | | 73F DB (23C) | | 80F DB (27C) | | 82F DB (28C) | |
|-------------|--------------|-----|--------------|-----|--------------|-----|--------------|-----|
| Coil air | 57F WB (14C) | | 61F WB (16C) | | 67F WB (19C) | | 68F WB (20C) | |
| DB | TC | SHC | TC | SHC | TC | SHC | TC | SHC |
| -22F(-30°C) | 8589 | | 8556 | | 8533 | | 8458 | |
| -13F(-25°C) | 9760 | | 9724 | | 9698 | | 9613 | |
| -4F(-20°C) | 12200 | | 12155 | | 12123 | | 12020 | |
| 0F(-17.7°C) | 12289 | | 12247 | | 12215 | | 12113 | |
| 6F(-14.4°C) | 13304 | | 13259 | | 13227 | | 13117 | |
| 10F(-12°C) | 13743 | | 13697 | | 13664 | | 13560 | |
| 16F(-8.9°C) | 14590 | | 14542 | | 14507 | | 14396 | |
| 19F(-7.2°C) | 14797 | | 14750 | | 14695 | | 14584 | |
| 24F(-4.4°C) | 15658 | | 15606 | | 15548 | | 15433 | |
| 32F(0°C) | 17094 | | 17037 | | 16979 | | 16857 | |
| 41F(5.8°C) | 18263 | | 18200 | | 18139 | | 18003 | |
| 43F(6.1°C) | 18410 | | 18359 | | 18297 | | 18159 | |
| 47F(8.3°C) | 17858 | | 17808 | | 17750 | | 17614 | |
| 53F(11.7°C) | 17322 | | 17275 | | 17220 | | 17088 | |
| 59F(15°C) | 16023 | | 15980 | | 15927 | | 15793 | |
| 64F(17.7°C) | 14773 | | 14734 | | 14685 | | 14561 | |
| 70F(21.1°C) | 13887 | | 13853 | | 13806 | | 13686 | |
| 75F(23.9°C) | 12915 | | 12884 | | 12740 | | 12580 | |
| 78F(25.6°C) | 12140 | | 12112 | | 12006 | | 11871 | |

TC – Total Capacity

SHC – Sensible Heat Capacity

BF – Bypass Factor

