

	Technical Specifications			
	Split Air Conditioner Outdoor Unit			
	Sr No	Parameter	Unit	Value
1	1	Model	—	BMKH18MC
2	2	Product Code	—	453094231
4	3	Cooling Capacity	kW	4.982
5	4	Cooling Capacity	Btu/h	17000
6	5	Min. Cooling Capacity	W	2052
7	6	Min. Cooling Capacity	Btu/h	7000
8	7	Max. Cooling Capacity	W	5744
9	8	Max. Cooling Capacity	Btu/h	19600
10	9	Heating Capacity	kW	5.275
11	10	Heating Capacity	Btu/h	18000
12	11	Min. Heating Capacity	W	2052
13	12	Min. Heating Capacity	Btu/h	7000
14	13	Max. Heating Capacity	W	5744
15	14	Max. Heating Capacity	Btu/h	19600
16	15	EER	W/W	3.52
17	16	EER	(Btu/h)/W	12.00
18	17	COP	W/W	3.82
19	18	COP	(Btu/h)/W	13.03
20	19	SEER2	—	21.00
21	20	HSPF2	—	10.00
30	21	Air Flow Volume	m3/h	2300.00
31	22	Air Flow Volume	CFM	1354

	Technical Specifications			
	Split Air Conditioner Outdoor Unit			
	Sr No	Parameter	Unit	Value
34	23	Sound Pressure Level	dB(A)	C:53/H:54
37	24	Sound Power Level	dB(A)	64.00
46	25	Rated Voltage	V	208/230
47	26	Rated Frequency	Hz	60
48	27	Phases	—	1.00
50	28	Cross-sectional Area of Power Cable Condu	mm2	2.1 (AWG14)
52	29	Recommended Power Cable(Core)	N	3.00
53	30	Fuse Current	A	20
54	31	Circuit Breaker	A	20
55	32	Cooling Power Input	kW	1.42
56	33	Heating Power Input	kW	1.38
57	34	Rated Power Input	kW	2.3/2.1
58	35	Cooling Current Input	A	6.28
59	36	Heating Current Input	A	6.12
60	37	Rated Current	A	10.0/9.0
61	38	Starting Current	A	5
66	39	Compressor Trademark	—	GREE
67	40	Compressor Manufacturer	—	ZHUHAI LANDA COMPRESSOR CO., LTD.
68	41	Compressor Model1	—	QXF-A139zH170A
70	42	Compressor Type1	—	Inverter Rotary
73	43	Compressor Capacity	W	4830

	Technical Specifications			
	Split Air Conditioner Outdoor Unit			
	Sr No	Parameter	Unit	Value
74	44	Compressor Power Input	W	1295
75	45	Compressor Rated Load Amp (RLA)	A	9.95
76	46	Compressor Locked Rotor Amp (L.R.A)	A	25
78	47	Compressor Thermal Protector	—	KSD115°C HPC115/95U1
79	48	Compressor Crankcase	W	/
80	49	Compressor Refrigerant Oil Type	—	FW68DA or equivalent
81	50	Compressor Refrigerant Oil Charge Volume	L	0.400
82	51	Chassis Electrical Heater Power Input	W	96
83	52	Chassis Electrical Heater Current	A	/
86	53	Fan Type	—	Axial-flow
87	54	Fan Quantity	—	1
88	55	Fan Diameter-height	mm	420-131.1
90	57	Motor Model	—	FW30R-ZL<10P>
91	58	Motor Type	—	DC motor
92	59	Motor Insulation Class	—	E
93	60	Motor Safe Class	—	IP24
94	61	Overload Protector	—	/
95	62	Motor Full Load Amp(FLA)	A	0.5
96	63	Fan Motor Drive Type	—	Direct drive
97	64	Fan Motor Speed	rpm	cooling900/heating900
98	65	Fan Motor Power Output	W	30
99	66	Fan Motor Power Input	W	/

	Technical Specifications			
	Split Air Conditioner Outdoor Unit			
	Sr No	Parameter	Unit	Value
100	67	Fan Motor Capacitor	μF	/
106	68	Condenser Material	—	Aluminum Fin-copper Tube
107	69	Condenser Face Area	m2	0.44
109	70	Condenser Pipe Diameter	in	0.31
111	71	Condenser Number of Rows	—	2
112	72	Condenser Tube Pitch(a)×Row Pitch(b)	in	0.75 x 0.87
114	73	Condenser Fin Pitch	in	0.06
117	74	Condenser Fin Type	—	波纹片
118	75	Condenser Fin Colour	—	blue
120	76	Condenser Length(L) × Height(H) × Width (W)	in	32.83 x 20.79 x 1.5
122	77	Condenser Max. Allowable Pressure	MPa	10.0
131	78	Permissible Excessive Operating Pressure for the Discharge Side	MPa	4.3
132	79	Permissible Excessive Operating Pressure for the Suction Side	MPa	2.5
133	80	Maximum Allowable Pressure	MPa	4.3
134	81	High Presser Overload Protector	MPa	/
135	82	Low Presser Overload Protector	MPa	/
136	83	Cooling Operation Ambient Temperature Range	°C	-22 ~ 118.4
138	84	Heating Operation Ambient Temperature Range	°C	-7.6 ~ 75.2
140	85	Maximum drive IDU NO.	unit	2
142	86	Defrosting Method	--	Automatic Defrosting

	Technical Specifications			
	Split Air Conditioner Outdoor Unit			
	Sr No	Parameter	Unit	Value
143	87	Isolation	—	I
144	88	Moisture Protection	--	IPX4
145	89	Overload Protector	—	/
146	90	Climate Type	—	T1
147	91	Refrigerant	—	R410A
148	92	Refrigerant Charge	lbs	2.86
150	93	Throttling Method	—	Electron expansion valve
161×163×165	94	Dimension of Outline(W×D×H)	in	32.36 x 13.86 x 21.65
167×169×171	95	Dimension of Carton Box(L×W×H)	in	34.21 x 15.55 x 23.39
173×175×177	96	Dimension of Package(L×W×H)	in	34.33 x 15.67 x 24.41
179	97	Net Weight	lbs	77.16
181	98	Gross Weight	lbs	82.67
183	99	Outdoor Unit Loading Quantity (20' Container)	unit	102.0
184	100	Outdoor Unit Loading Quantity (40' Container)	unit	213.0
185	101	Outdoor Unit Loading Quantity (40' High Cube Container)	unit	284.0
191	102	Connection Pipe Connection Method	—	Flare Connection
192	103	Not Additional Gas Connection Pipe Length	ft	32.8
194	104	Connection Pipe Gas Additional Charge	g/m	20
196	105	Connection Pipe Liquid Pipe Outer Diameter 1	in	1/4
198	106	Connection Pipe Liquid Pipe Outer Diameter 2	in	1/4

	Technical Specifications			
	Split Air Conditioner Outdoor Unit			
	Sr No	Parameter	Unit	Value
200	107	Connection Pipe Liquid Pipe Outer Diameter 3	in	/
202	108	Connection Pipe Liquid Pipe Outer Diameter 4	in	/
204	109	Connection Pipe Liquid Pipe Outer Diameter 5	in	/
206	110	Connection Pipe Gas Pipe Outer Diameter 1	in	3/8
208	111	Connection Pipe Gas Pipe Outer Diameter 2	in	3/8
210	112	Connection Pipe Gas Pipe Outer Diameter 3	in	/
212	113	Connection Pipe Gas Pipe Outer Diameter 4	in	/
214	114	Connection Pipe Gas Pipe Outer Diameter 5	in	/
216	115	Connection Pipe Max. Height Distance (indoor and indoor)	ft	49.21
218	116	Connection Pipe Max. Height Distance (indoor and outdoor and indoor up)	ft	49.21
220	117	Connection Pipe Max. Height Distance (indoor and outdoor and outdoor up)	ft	49.21
222	118	Max. equivalent connection pipe length (outdoor to last indoor)	ft	65.61
224	119	Connection Pipe Max. Length Distance (total length)	ft	131.23
	Air Condition Function			
241	120	Low Ambient Cooling Function		YES
242	121	Defrosting Time Set Function		NO
243	122	Low Voltage Startup		YES
244	123	Compressor With Electric Heater		NO

	Technical Specifications			
	Split Air Conditioner Outdoor Unit			
	Sr No	Parameter	Unit	Value
245	124	Chassis With Electric Heater		YES