

Heating

Outdoor	68F DB (20C)		73F DB (23C)		80F DB (27C)		82F DB (28C)	
Coil air	57F WB (14C)		61F WB (16C)		67F WB (19C)		68F WB (20C)	
DB	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-22F (-30°C)	14194		13955		13699		13391	
-13F (-25°C)	18752		18437		18098		17692	
-4F (-20°C)	23362		22969		22547		22041	
0F (-17. 7°C)	24013		23614		23161		22641	
6F (-14. 4°C)	24233		23826		23379		22844	
10F (-12°C)	24726		24313		23851		23314	
16F (-8. 9°C)	25215		24795		24313		23769	
19F (-7. 2°C)	25697		25277		24782		24226	
24F (-4. 4°C)	25909		25517		25080		24576	
32F (0°C)	26103		25750		25356		24902	
41F (5. 8°C)	27424		27102		26723		26297	
43F (6. 1°C)	27972		27642		27276		26852	
47F (8. 3°C)	29278		28771		28191		27521	
53F (11. 7°C)	29568		29052		28472		27793	
59F (15°C)	30248		29713		29115		28427	
64F (17. 7°C)	30891		30347		29740		29034	
70F (21. 1°C)	31470		30927		30302		29586	
75F (23. 9°C)	31914		31353		30728		29994	
78F (25. 6°C)	32360		31790		31156		30412	

TC – Total Capacity
SHC – Sensible Heat Capacity
BF – Bypass Factor

..

.....

