

# SUBMITTAL DATA SHEET



| BMM12LW             | New Console         |
|---------------------|---------------------|
| Location: _____     | Approval: _____     |
| Engineer: _____     | Date: _____         |
| Submitted to: _____ | Construction: _____ |
| Submitted by: _____ | Unit #: _____       |
| Reference: _____    | Drawing #: _____    |

|                   |           |
|-------------------|-----------|
| Indoor unit code  | 453091301 |
| Indoor unit model | BMM12LW   |
| Certified         | UL        |



| INDOOR UNIT DATA           |             |                     |  |
|----------------------------|-------------|---------------------|--|
| <b>Power supply</b>        |             |                     |  |
| Normal Operational Voltage | (V, Ph, Hz) | 208-230V, 1Ph, 60Hz |  |
| Voltage Range              | (V)         | 187-253             |  |
| <b>Indoor fan motor 1</b>  |             |                     |  |
| Type                       |             | Cross-Flow          |  |
| Model                      |             | ZKFP-13-8-136       |  |
| Qty                        |             | 1                   |  |
| Input                      | (W)         | /                   |  |
| Output                     | (W)         | 13                  |  |
| RLA                        | (A)         | 0.50                |  |
| Speed(Hi/Mi/Lo)            | (r/min)     | 992/884/776         |  |
| <b>Indoor fan motor 2</b>  |             |                     |  |
| Type                       |             | Cross-Flow          |  |
| Model                      |             | ZKFP-13-8-104       |  |
| Qty                        |             | 1                   |  |
| Input                      | (W)         | /                   |  |
| Output                     | (W)         | 13                  |  |
| RLA                        | (A)         | 0.50                |  |
| Speed(Hi/Mi/Lo)            | (r/min)     | 992/884/776         |  |

| INDOOR UNIT DATA                  |          |                      |  |
|-----------------------------------|----------|----------------------|--|
| <b>Air flow &amp; Noise level</b> |          |                      |  |
| Indoor air flow (Hi/Med/Lo)       | (CFM)    | 376.47/323.53/264.71 |  |
| Indoor noise level (Hi/Med/Lo)    | [dB(A)]  | 40/37/26             |  |
| <b>Dehumidification</b>           |          |                      |  |
|                                   | (Pint/H) | ---                  |  |
| <b>Indoor unit</b>                |          |                      |  |
| Dimension (WxDxH)                 | (inch)   | 31.26x7.87x24.45     |  |
|                                   | (mm)     | 794x200x621          |  |
| Packing(WxDxH)                    | (inch)   | 34.06x11.02x28.31    |  |
|                                   | (mm)     | 865x280x719          |  |
| Net/Gross weight                  | (lbs.)   | 32.85/41.45          |  |
|                                   | (kg)     | 14.9/18.8            |  |
| Liquid side/ Gas side             | (inch)   | 1/4" / 1/2"          |  |
|                                   | (mm)     | 6.35/12.7            |  |

