

# SUBMITTAL DATA SHEET



<b>BMM12WM</b>	<b>Wall Mounted Heat Pump Air Handlers</b>
Location: _____	Approval: _____
Engineer: _____	Date: _____
Submitted to: _____	Construction: _____
Submitted by: _____	Unit #: _____
Reference: _____	Drawing #: _____

Indoor unit code	453083716
Indoor unit model	BMM12WM
Certified	UL  US LISTED



INDOOR UNIT DATA		
<b>Power supply</b>		
Normal Operational Voltage	(V, Ph, Hz)	208/230, 1, 60
Voltage Range	(V)	187-253
<b>Indoor fan motor</b>		
Type		Cross-Flow
Model		ZKFP-13-8-4
Qty		1
Input	(W)	-
RLA	(A)	-
LRA	(A)	-
Winding Resistance	(Ω)	-
Capacitor	(uF)	-
Speed(Hi/Mi/Lo)	(r/min)	1250/950/750

INDOOR UNIT DATA		
<b>Air flow &amp; Noise level</b>		
Indoor air flow (Hi/Med/Lo)	(CFM)	495/330/260
Indoor noise level (Hi/Med/Lo)	[dB(A)]	41.5/36/24
<b>Dehumidification</b>	(Pint/H)	---
<b>Indoor unit</b>		
Dimension (WxDxH)	(inch)	31.57x7.87x11.61
	(mm)	802x200x295
Packing(WxDxH)	(inch)	34.45x11.22x14.96
	(mm)	875x285x380
Net/Gross weight	(lbs.)	18.74/24.25
	(kg)	8.5/11
<b>Liquid side/ Gas side</b>	(inch)	1/4" / 1/2"
	(mm)	Φ6.35 / Φ12.7
<b>Application area</b>	(sq.ft)	172.22 ~ 247.57
	(m2)	16 ~ 23

**Indoor unit dimension**

Capacity	Body Code	W(mm/inch)	D(mm/inch)	H(mm/inch)
6K~11K	A	729/28.7	200/7.87	292/11.5
8K~14K	B	802/31.57	200/7.87	295/11.61
12K~21K	C	971/38.23	228/8.98	321/12.64
18K~28K	D	1082/42.6	234/9.21	337/13.27
27K~36K	F	1259/49.57	283/11.14	362/14.25