

SUBMITTAL DATA SHEET



Multi Zone Heat Pump

Location: _____
 Engineer: _____
 Submitted to: _____
 Submitted by: _____
 Reference: _____

Approval: _____
 Date: _____
 Construction: _____
 Unit #: _____
 Drawing #: _____


Outdoor unit code 22022316001345
 Outdoor unit model BMM18C

Certified

AHRI



UL



SYSTEM PERFORMANCE DATA

Power supply

Normal Operational Voltage (V, Ph, Hz) 208/230V, 1Ph, 60Hz
 Voltage Range (V) 187-253

Electrical

Minimum circuit ampacity (A) 14.0
 Max.fuse (A) 20.0
 Connection wiring 14AWG*4 Stranded, unshielded

Cooling

Capacity (Btu/h) 18000(4950~23000)
 Power Input (W) 1440(217~2026)
 Current (A) 6.4(1.76~8.91)
 SEER2 (Btu/W) 21.0
 EER2 (Btu/W) 12.5

Heating

Capacity (Btu/h) 19000(4900~23000)
 Power Input (W) 1550(317~1959)
 Current (A) 6.7(2.41~8.61)
 HSPF2-4 (Btu/W) 10.2
 HSPF2-5 (Btu/W) 7.7
 COP W/W 3.59
 Heat at 17F(H32) (Btu/h) 14400
 Heat at 5F(H42) (Btu/h) 12600
 COP at 5F(H42) W/W 2.00

REFRIGERANT PIPE DATA

Design pressure (PSIG) 550/340
 Refrigerant Type R410A
 Refrigerant charge oz 65.3
 Refrigerant precharge (ft) 25x2
 Additional charge for each ft (Φ6.35 (1/4") liquid pipe) (oz/ft) 0.16
 (g/ft) 15.0
 Additional charge for each ft (Φ9.52 (3/8") liquid pipe) (oz/ft) 0.32
 (g/ft) 30.0
 Liquid side (inch) 2x1/4"
 (mm) 2x6.35
 Gas side (inch) 2x3/8"
 (mm) 2x9.52
 Max. length for all rooms (ft) 131.2
 (m) 40.0
 Max. length for one indoor unit (ft) 82.0
 (m) 25.0
 Max. height difference between indoor and outdoor unit (ft) 49.2
 (m) 15.0
 Max. height difference between indoor units (ft) 33.0
 (m) 10.0

Outdoor(cooling) (Deg. F) 5~122
 (Deg. °C) -15~50
 Outdoor(heating) (Deg. F) -13~75
 (Deg. °C) -25~24

OUTDOOR UNIT DATA

Compressor

Type Twin-ROTARY
 Model KTN150D30UFZA
 Brand GMCC
 Capacity (Btu/h) 16139
 Input (W) 1250
 Rated current (RLA) (A) /
 Refrigerant oil/oil charge (ml) ESTER OIL VG74 450

Outdoor fan motor

Model ZKFN-80-8-3
 Qty 1
 Input (W) /
 Output (W) 80.00
 RLA (A) /
 Speed (r/min) 750/600/500

Air flow & Noise level

Outdoor air flow (Max.) (CFM) 1764.71
 Outdoor noise level [dB(A)] 59.50

Outdoor unit

Dimension (W×D×H) (inch) 35.04x13.46x26.50
 (mm) 890x342x673
 Packing (W×D×H) (inch) 40.55x17.24x29.53
 (mm) 1030x438x750
 Net/ Gross weight (lbs.) 100.31/108.69
 (kg) 45.5/49.3

Outdoor unit dimension

