## SUBMITTAL DATA SHEET



Multi Zone Heat Pump				
	Approval:			
Location:	Date:			
Engineer:	Construction:			
Engineer:Submitted to:	Unit #:			
Submitted by:Reference:	Drawing #:			
Reference:				
Reference:	_			

Outdoor unit code

22022316001646

Outdoor unit model

BMM48C Non-Ducted

Ceritified

AHRI


UL

CUL

USUSUSTED



Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60Hz
Voltage Range	(V)	187-253
Electrical		
Minimum circuit ampacity	(A)	40.0
Max.fuse	(A)	60.0
Connection wiring		14AWG*4 Stranded, unshielded
Cooling		
Capacity	(Btu/h)	48000(11600~49700)
Power Input	(W)	4440(810~4730)
Current	(A)	19.97(3.9~20.7)
SEER2	(Btu/W)	21.1
EER2	(Btu/W)	11.0
Heating		
Capacity	(Btu/h)	48000(33000~52900)
Power Input	(W)	4390(2860~4750)
Current	(A)	19.97(12.7~20.8)
HSPF2-4	(Btu/W)	9.5
COP	W/W	3.20
Heat at 17F(H32)	(Btu/h)	36000
Heat at 5F(H42)	(Btu/h)	33000
COP at 5F(H42)	`W/W	1.80



REFRIGERANT PIPE DATA  Design pressure	(PSIG)	550/340
Refrigerant Type	(* 5.5)	R410A
Refrigerant charge	OZ	162.0
Refrigerant precharge	(ft)	25x5
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	5x1/4'
Gas side	(inch)	3x3/8"+2x1/2"
Max. length for all rooms	(ft)	262.5
Max. length for one indoor unit	(ft)	114.8
Max. height difference between indoor and outdoor unit	(ft)	49.2
Max. height difference between indoor units	(ft)	33.0

OUTDOOR UNIT DATA		
Compressor		
Туре		ROTARY
Model		ATQ360D1UMU
Brand		GMCC
Capacity	(Btu/h)	38214
Input	(W)	3040
Rated current (RLA)	(A)	24
Refrigerant oil/oil charge	(ml)	VG74/1400
Outdoor fan motor		
Model		ZKFN-85-8-22-5
Qty		2
Input	(W)	126.00
Output	(W)	85.00
RLA	(A)	2.50
Speed	(r/min)	900/850/800/750
Air flow & Noise level		
Outdoor air flow (Max.)	(CFM)	4500.00
Outdoor noise level	[dB(A)]	62.00
Outdoor unit		
Dimension (W×D×H)	(inch)	37.48x16.34x52.48
Packing (W×D×H)	(inch)	43.11x19.49x58.27

