## SUBMITTAL DATA SHEET



Multi Zone Heat Pump				
	Approval:			
Location:	Date:			
Engineer:Submitted to:	Construction:			
Submitted to:	Unit #:			
Submitted by:	Drawing #:			
Reference:				
	<del></del>			

Outdoor unit code

22022316001766

Outdoor unit model

BMM55HHC Non-Ducted

Ceritified

AHRI

UL

UL

ENERGY STAR



LISTED				
EVETEM DEDECORMANCE D	ATA			
SYSTEM PERFORMANCE D Power supply	AIA			
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60Hz		
Voltage Range	(V, FII, FIZ) (V)	187-253		
Vollage Range	(V)	107-233		
Electrical				
Minimum circuit ampacity	(A)	40.0		
Max.fuse	(A)	60.0		
Connection wiring		14AWG*4 Stranded, unshielded		
Cooling				
Capacity	(Btu/h)	55000(11600~56500)		
Powrer Input	(W)	5238(810~5800)		
Current	(A)	23.5(3.9~26)		
SEER2	(Btu/W)	20.0		
EER2	(Btu/W)	10.5		
Heating	(5, ")			
Capacity	(Btu/h)	55000(33000~63000)		
Powrer Input	(W)	5117(2860~5650)		
Current	(A)	22.5(12.7~25.5)		
HSPF2-4	(Btu/W)	9.3		
COP	W/W	3.15		
Heat at 17F(H32)	(Btu/h)	34800		
Heat at 5F(H42)	(Btu/h)	45500		
COP at 5F(H42)	W/W	1.80		
REFRIGERANT PIPE DATA				
Design pressure	(PSIG)	550/340		
Refrigerant Type	, ,	R410A		
Refrigerant charge	OZ	162.3		
Refrigerant precharge	(ft)	25x5		
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16		
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32		
Liquid side	(inch)	5x1/4'		
Gas side	(inch)	3x3/8"+2x1/2"		
Max. length for all rooms	(ft)	262.5		
Max. length for one indoor unit	(ft)	114.8		
Max. height difference between indoor and outdoor unit	(ft)	49.2		
Max. height difference between indoor units	(ft)	33.0		

Outdoor(cooling)	(Deg. °F)	5~12
Outdoor(heating)	(Deg. °F)	-22~75
OUTDOOR UNIT DAT	ГА	

	ROTARY
	EAPQ420D1UMUA
	GMCC
(Btu/h)	44015
(W)	3565
(A)	25
(ml)	1460±15mlESTER OIL VG74
	ZKFN-85-8-22-5
	2
(W)	126.00
(W)	85.00
(A)	2.50
(r/min)	900/850/800/750
(CFM)	4500.00
[dB(A)]	62.00
(inch)	37.48x16.34x52.48
(inch)	43.11x19.49x58.27
(lbs.)	233.03/265.87
	(W) (A) (MI)  (W) (W) (A) (r/min)  (CFM) [dB(A)]

Outdoor unit dimension

