

SUBMITTAL DATA SHEET



BMM9CC2	One Way Cassette
Location: _____	Approval: _____
Engineer: _____	Date: _____
Submitted to: _____	Construction: _____
Submitted by: _____	Unit #: _____
Reference: _____	Drawing #: _____

Indoor unit code	453091297
Indoor unit model	BMM9CC2
Certified	UL



INDOOR UNIT DATA		
Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V, 1Ph, 60Hz
Voltage Range	(V)	187-253
Indoor fan motor		
Type		Cross-Flow
Model		ZKFN-30-8-43
Qty		1
Input	(W)	/
Output	(W)	30
RLA	(A)	0.8
Speed(Hi/Mi/Lo)	(r/min)	1024/944/784

INDOOR UNIT DATA		
Air flow & Noise level		
Indoor air flow (Hi/Med/Lo) (No)	(CFM)	294.12/258.82/235.29
Indoor noise level (Hi/Med/Lo)	[dB(A)]	37.5/35.5/31
Dehumidification	(Pint/H)	---
Indoor unit		
Dimension (WxDxH)	(inch)	50.31x13.19x8.98
	(mm)	1278x335x228
Packing(WxDxH)	(inch)	57.60x22.48x22.64
	(mm)	1463x571x575
Net/Gross weight	(lbs.)	43.87/81.35
	(kg)	19.9/36.9
Liquid side/ Gas side	(inch)	1/4" / 3/8"
	(mm)	6.35/9.52

