Technical Features of *Blueridge PTAC Series* BPM07 BPM09 BPM12 BPM 15



➤ Air exchange



PTAC-INTERIOR

PTAC-EXTERIOR

LED Display



> Auto-Restart





If the air conditioner shuts off unexpectedly due to the power off, it will restart to work under the previous setting mode automatically when the power resumes.

> Auto-defrosting function





Prevent evaporator from freezing, prolong product life and improve energy saving.

Wired control (Optional)

It is a optional function. With or without Clock, Timer function. Wire length: 0.85m; White (default) or silver Size: 235*160*95 mm

Wireless controller





24 Voltage Universal controller, Include Wired controller with weekly program (24V control) and wireless controller.

Electric heater (Optional)



The PTAC has two different electric heaters:

One is the standard heater, it just has one output capacity, another is optional heater, it has two different output capacity, and it is easy to be change by the power cord.

> Health design (Optional)

Large ventilation door: let more fresh air into the room, and make quick air exchange.



open



close

- Normal filter
- Antibacterial filter (Optional)

Filter placed in a position easy to clean



Accessory (Optional)



Drain Kit (is included in box)



Extruded architectural grille





Wall sleeve

Aluminum grille

> Features



Cooling and Heating Cooling and Electric heater Power supply 7K 9K 12K 15K 15K 15K

230V	—	—	0

Refrigerant:R410A

Product Lineup