

# SUBMITTAL DATA SHEET

Model BXAFA12LW0 - Indoor Air Handler Unit

## AIR HANDLER SPECIFICATION

<b>Model Number</b>	BXAFA12LW0
<b>Cooling Capacity (Nominal)</b>	12,000 BTU/hr
<b>Heating Capacity (Nominal)</b>	12,000 BTU/hr
<b>Indoor Air Flow (Turbo/Hi/Mi/Lo/Si)</b>	441.4 / 376.7 / 323.7 / 188.4 / 129.5 CFM
<b>Indoor Noise Level (Turbo/Hi/Mi/Lo/Si)</b>	44 / 40.5 / 37.0 / 26.5 / 24.0 dB(A)
<b>Dimension (W x D x H)</b>	31.26 x 7.87 x 24.45 inch
<b>Net/Gross Weight</b>	32.85 / 41.89 lb

## ELECTRICAL

<b>Indoor Fan Motor RLA</b>	0.5 A
<b>Indoor Fan Motor Output</b>	13 W
<b>Minimum Circuit Ampacity (Indoor)</b>	3.00 A
<b>Maximum Fuse (Indoor)</b>	15 A
<b>Connection Wiring</b>	14#x4

## PIPING

<b>Refrigerant Type</b>	R454B
<b>Liquid Side Connection</b>	1/4" (6.35 mm)
<b>Gas Side Connection</b>	3/8" (12.7 mm)

### Abbreviations:

- dB(A) = Decibels (A-weighted)
- CFM = Cubic Feet per Minute
- BTU/hr = British Thermal Units per Hour
- RLA = Rated Load Amperage
- A = Amperes
- W = Watts
- R454B = Low Global Warming Potential Refrigerant