

SUBMITTAL DATA SHEET

8-Way Cassette Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION

Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	330 / 318 / 288 / 265 / 247 / 224 / 206	
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	40 / 38 / 35 / 34 / 32 / 30 / 27	
Dimension (W×D×H)	inch	22.56 x 22.56 x 10.47
Package (W×D×H)	inch	22.36 x 25.59 x 11.03
Net/Gross Weight	lbs	37.5

OUTDOOR SPECIFICATION

Compressor Type	Rotary	
Compressor Model	QXF-B103zH170E	
Refrigerant	R32	
Refrigerant Oil	RB68EP	
Outdoor Air Flow (Max) (CFM)	1295.0	
Outdoor Noise Level (dBA)	52	
Dimension (W×D×H)	inch	31.58 x 21.84 x 13.78
Package (W×D×H)	inch	34.22 x 15.55 x 23.39
Net/Gross Weight	lbs	70.6 / 76.1

EFFICIENCY

Cooling		Heating	
SEER2	24	HSPF2-4	9.2
EER2	15	COP	3.9

PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	9100
Min/Max Capacity	2559 / 12624
Moisture Removal(L/h)	0.8
Standard Operating Range(°F)	-20~122

PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47°F Rated	10500
1. @ 47°F Min/Max Capacity	2900 / 13648
Standard Operating Range(°F/°C)	-22~86

ELECTRICAL

Power Supply	208/230V - 1 Ph - 60Hz
System MCA	10
Connection Wiring	14#4
System MOCP	15
Compressor RLA	6.5
Outdoor Fan Motor RLA	0.96
Outdoor Fan Motor W	30
Indoor Fan Motor RLA	0.5
Indoor Fan Motor W	30
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING

Throttle type(Indoor)	N/A
Throttle type(Outdoor)	Electron expansion valve
Liquid Size	1/4
Gas Size	3/8
Max. Piping Length(ft/m)	65
Max. Height Difference(ft/m)	40
Max. Pre-charged Length(ft/m)	25
Refrigerant Pre-charged Amount(oz)	30
Additional Charge of Refrigerant((oz/ft))	0.2
Connection Method	Flared