

# SUBMITTAL DATA SHEET

## Console Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



### INDOOR SPECIFICATION

Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	441 / 383 / 353 / 324 / 294 / 265 / 206	
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	45 / 42 / 39 / 37 / 35 / 32 / 25	
Dimension (W×D×H)	inch	27.56 x 23.63 x 8.47
Package (W×D×H)	inch	30.91 x 11.03 x 26.84
Net/Gross Weight	lbs	33.1

### OUTDOOR SPECIFICATION

Compressor Type	Rotary	
Compressor Model	QXF-M098zE170	
Refrigerant	R32	
Refrigerant Oil	FW68L	
Outdoor Air Flow (Max) (CFM)	1295.0	
Outdoor Noise Level (dBA)	52	
Dimension (W×D×H)	inch	31 x 21.84 x 13.78
Package (W×D×H)	inch	34.22 x 15.55 x 23.38
Net/Gross Weight	lbs	67.3

### EFFICIENCY

Cooling		Heating	
SEER2	23	HSPF2-4	9.0
EER2	13	COP	3.8

### PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	12000
Min/Max Capacity	2730 / 13307
Moisture Removal(L/h)	1.4
Standard Operating Range(℉/℃)	-20~122

### PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47℉ Rated	12000
1. @ 47℉ Min/Max Capacity	3070 / 13989
Standard Operating Range(℉/℃)	-22~86

### ELECTRICAL

Power Supply	208/230V - 1 Ph - 60Hz
System MCA	10
Connection Wiring	14#4
System MOCP	15
Compressor RLA	7
Outdoor Fan Motor RLA	0.7
Outdoor Fan Motor W	30
Indoor Fan Motor RLA	N/A
Indoor Fan Motor W	30
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

### PIPING

Throttle type(Indoor)	N/A
Throttle type(Outdoor)	Electron expansion valve
Liquid Size	1/4"
Gas Size	3/8"
Max. Piping Length(ft/m)	65.6
Max. Height Difference(ft/m)	40
Max. Pre-charged Length(ft/m)	25
Refrigerant Pre-charged Amount(oz)	28.2
Additional Charge of Refrigerant((oz/ft))	0.2
Connection Method	Flared