

SUBMITTAL DATA SHEET

Slim Duct Heat Pump System	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION		
Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	883 / 530 / 441 / 383	
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	40 / 32 / 26 / 24	
Dimension (WxDxH)	inch	44.48 x 11.81 x 29.69
Package (WxDxH)	inch	47.33 x 31.89 x 13.58
Net/Gross Weight	lbs	92.6

OUTDOOR SPECIFICATION		
Compressor Type	Rotary	
Compressor Model	QXF-M130zF170	
Refrigerant	R32	
Refrigerant Oil	FW68DA or equivalent	
Outdoor Air Flow (Max) (CFM)	2119.0	
Outdoor Noise Level (dBA)	59	
Dimension (WxDxH)	inch	37.72 x 25.98 x 15.83
Package (WxDxH)	inch	40.51 x 17.83 x 28.16
Net/Gross Weight	lbs	94.8

EFFICIENCY			
Cooling		Heating	
SEER2	22.5	HSPF2-4	9.0
EER2	14	COP	4.4

PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	18000
Min/Max Capacity	5118 / 23543
Moisture Removal(L/h)	1.8
Standard Operating Range(°F/°C)	-20~122

PERFORMANCE of Heating	
Heating (Btu/hr)	
1. @ 47°F Rated	18000
1. @ 47°F Min/Max Capacity	4265 / 23884
Standard Operating Range(°F/°C)	-22~86

ELECTRICAL	
Power Supply	208/230V - 1 Ph - 60Hz
System MCA	16
Connection Wiring	14#4
System MOCP	20
Compressor RLA	10.35
Outdoor Fan Motor RLA	1.35
Outdoor Fan Motor W	60
Indoor Fan Motor RLA	N/A
Indoor Fan Motor W	200
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

PIPING	
Throttle type(Indoor)	N/A
Throttle type(Outdoor)	Electron expansion valve
Liquid Size	1/4"
Gas Size	5/8"
Max. Piping Length(ft/m)	131.2
Max. Height Difference(ft/m)	82
Max. Pre-charged Length(ft/m)	25
Refrigerant Pre-charged Amount(oz)	40.6
Additional Charge of Refrigerant((oz/ft))	0.2
Connection Method	Flared