

| Capacity | | | 9K | 12K | 18K | 24K |
|--|-------------------------------|-------------|------------------------------|------------------------------|------------------------------|------------------------------|
| Indoor unit code | | | 453083715 | 453083716 | 453083717 | 453083718 |
| Indoor unit model | | | BMM9WM | BMM12WM | BMM18WM | BMM24WM |
| Customer Indoor unit model | | | | | | |
| Customer Outdoor unit model | | | | | | |
| Power supply | Rated | V, Ph, Hz | 208/230, 1, 60 | 208/230, 1, 60 | 208/230, 1, 60 | 208/230, 1, 60 |
| | Voltage range | V | 187-253 | 187-253 | 187-253 | 187-253 |
| Cooling | Rated Capacity (range) | Btu/h | 9000(3700~13300) | 12000(3700~13300) | 18000(8400~20200) | 23000(4650~26600) |
| | Input power | W | 569 | 923 | 1385 | 1840 |
| | Rated current | A | 2.5 | 2.5 | 8.9 | 8.25 |
| | EER | Btu/w | 15.8 | 13 | 13 | 12.5 |
| | SEER | Btu/w | 25.5 | 22 | 21.5 | 21.5 |
| Heating at 47F | Rated Capacity (range) | Btu/h | 12000(5100~14300) | 12000(5100~14300) | 18000(12000~23000) | 26000(9550~27000) |
| | Input power | W | 902 | 978 | 1575 | 2540 |
| | Rated current | A | 4.0 | 4.25 | 9.2 | 11.38 |
| | COP | W/W | 3.90 | 3.60 | 3.35 | 3 |
| | HSPF4 | Btu/w | 12.5 | 12.7 | 11 | 11.5 |
| | HSPF5 | Btu/w | 10.5 | 10.8 | 9.2 | 9.7 |
| Heating at 17F (AHRI) | Rated capacity | Btu/h | 12000 | 12000 | 19000 | 23000 |
| Heating at 5F (-15°C) | Rated capacity | Btu/h | 10000 | 10000 | 18000 | 23000 |
| | COP | W/W | 1.8 | 1.8 | 1.78 | 1.75 |
| MAX. FUSE (Indoor unit) | | A | 15.0 | 15.0 | 15.0 | 15.0 |
| Indoor fan motor | Model | | ZKFP-13-8-4 | ZKFP-13-8-4 | ZKFP-58-8-1-5 | ZKFP-58-8-1-5 |
| | Qty. | | 1 | 1 | 1 | 1 |
| | Input power | W | - | - | 58.0 | 58.0 |
| | Output power | W | 13.0 | 13.0 | | 58.0 |
| | Fan motor load current (RLA) | A | - | - | - | - |
| | Speed(Hi/Mi/Lo) | r/min | 1150/990/750 | 1250/950/750 | 1120/950/700 | 1200/1080/600 |
| Indoor air flow (Hi/Mi/Lo) | | m3/h | 495/330/260 | 495/330/260 | 902/780/650 | 1022/780/650 |
| Indoor air flow (Hi/Mi/Lo) | | CFM | 291.18/194.12/152.94 | 291.18/194.12/152.94 | 530.59/458.82/382.35 | 601.18/458.82/382.35 |
| Indoor noise level (Hi/Mi/Lo) | | dB(A) | 40/35/23.5 | 41.5/36/24 | 46/40/25 | 46.5/44/35 |
| Evaporator | Number of rows | / | 2 | 2 | 2 | 2 |
| | Tube outside dia | mm | Φ7 | Φ7 | Φ7 | Φ7 |
| | Tube outside type | / | Inner groove tube | Inner groove tube | Inner groove tube | Inner groove tube |
| | Tube pitch(a)x row pitch(b) | mm | 21x13.37 | 21x13.37 | 21x13.37 | 21x13.37 |
| | Fin spacing | mm | 1.3 | 1.3 | 1.3 | 1.3 |
| | Fin type (code) | / | Hydrophilic aluminum | Hydrophilic aluminum | Hydrophilic aluminum | Hydrophilic aluminum |
| | Coil length x height x width | mm | 605x210x26.74+605x105x26.74 | 605x210x26.74+605x105x26.74 | 820x210x26.74+820x126x26.74 | 820x210x26.74+820x126x26.74 |
| Number of circuits | / | 2 | 2 | 4 | 4 | |
| Indoor unit | Dimension(W*D*H) | mm | 802x200x295 | 802x200x295 | 1082x234x337 | 1082x234x337 |
| | | inch | 31.57x7.87x11.61 | 31.57x7.87x11.61 | 42.64x9.61x13.23 | 42.60x9.21x13.27 |
| | Packing (W*D*H) | mm | 875x285x380 | 875x285x380 | 1155x415x315 | 1155x415x315 |
| | | inch | 34.45x11.22x14.96 | 34.45x11.22x14.96 | 45.47x16.34x12.40 | 45.47x16.34x12.40 |
| Net/Gross weight | Kg | 8.6/11 | 8.5/11 | 13.4/17 | 13.6/17.3 | |
| | lbs. | 18.96/24.25 | 18.74/24.25 | 29.54/37.48 | 29.98/38.14 | |
| Refrigerant piping | Liquid side/Gas side | mm | Φ6.35 / Φ9.52 | Φ6.35 / Φ12.7 | Φ6.35 / Φ12.7 | Φ9.52 / Φ15.9 |
| | | inch | 1/4" / 3/8" | 1/4" / 1/2" | 1/4" / 1/2" | 3/8" / 5/8" |
| Connection wiring | | | 16AWG*4 Stranded, unshielded | 16AWG*4 Stranded, unshielded | 16AWG*4 Stranded, unshielded | 16AWG*4 Stranded, unshielded |
| Communication protocol between IDU and ODU | | | Current loop | Current loop | Current loop | Current loop |
| Thermostat type | Wireless remote controller | | Standard | Standard | Standard | Standard |
| | Wired Controller | | Optional | Optional | Optional | Optional |
| | Programmable wired Controller | | Optional | Optional | Optional | Optional |
| | WiFi | | Optional | Optional | Optional | Optional |
| Ambient temperature | Cooling | °C | 16~32 | 16~32 | 16~32 | 16~32 |
| | | °F | 60~90 | 60~90 | 60~90 | 60~90 |
| | Heating | °C | 0~27 | 0~30 | 0~30 | 0~30 |
| | | °F | 32~80.6 | 32~86 | 32~86 | 32~86 |
| Application area (cooling Standard) | | m2 | 12~18 | 16~23 | 24~35 | 31~45 |
| | | sq.ft | 129.17~193.75 | 172.22~247.57 | 258.33~376.74 | 333.68~484.38 |
| Qty. per 20'/40'/40' HQ | Indoor | | | | | |
| Qty. per 20'/40'/40' HQ | Set | | 90/190/222 | 90/190/222 | 64/134/156 | 44/90/113 |