## SUBMITTAL DATA SHEET



Multi Zone Heat Pump				
Approval:				
Date:				
Construction:				
Drawing #:				
	Construction:			

Outdoor unit code
Outdoor unit model

BMM18C
Mixed ducted
and non ducted
indoor units

Ceritified


AHRI
UL

CUL

UL

CUL

ENERGY STAR



SYSTEM PERFORMANCE	E DATA	
Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60Hz
Voltage Range	(V)	187-253
Electrical		
Minimum circuit ampacity	(A)	18.0
Max.fuse	(A)	25.0
Connection wiring		14AWG*4 Stranded, unshielded
Cooling		
Capacity	(Btu/h)	18000(4400~22700)
Power Input	(W)	1470(169~2050)
Current	(A)	6.6(1.55~9.11)
SEER2	(Btu/W)	20
EER2	(Btu/W)	12.25
Heating		
Capacity	(Btu/h)	19000(4625~24400)
Power Input	(W)	1544(326~2025)
Current	(A)	6.6(2.53~9)
HSPF2-4	(Btu/W)	10
COP	W/W	3.6
Heat at 17F(H32)	(Btu/h)	14600
Heat at 5F(H42)	(Btu/h)	12900
COP at 5F(H42)	W/W	2.00

Heat at 5F(H42)	(Btu/h)	12900
COP at 5F(H42)	W/W	2.00
REFRIGERANT PIPE DATA		
Design pressure	(PSIG)	550/340
Refrigerant Type		R410 <i>A</i>
Refrigerant charge	OZ	65.3
Refrigerant precharge	(ft)	49.0
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	2x1/4
Gas side	(inch)	2x3/8
Max. length for all rooms	(ft)	131.2
Max. length for one indoor unit	(ft)	82.0
Max. height difference between indoor and outdoor unit	(ft)	49.2
Max. height difference between indoor units	(ft)	33.0



Twin-ROTARY KTN150D30UFZA GMCC 16139 1250 / ESTER OIL VG74 450
KTN150D30UFZA GMCC 16139 1250 / ESTER OIL VG74 450
KTN150D30UFZA GMCC 16139 1250 / ESTER OIL VG74 450
GMCC 16139 1250 / ESTER OIL VG74 450
16139 1250 / ESTER OIL VG74 450
1250 / ESTER OIL VG74 450
ESTER OIL VG74 450
7KFN-80-8-3
7KEN-80-8-3
1
/
80.00
/
750/600/500
1764.71
59.50
35.04x13.46x26.50
40.55x17.24x29.53
100.31/108.69

