SUBMITTAL DATA SHEET



Multi Zone Heat Pump	
	Approval:
Location:	Date:
Engineer:	Construction:
Submitted to:	Unit #:
Submitted by:	Drawing #:
Reference:	

Outdoor unit code	22022316001865
Outdoor unit model	BMM27HH2C (Ducted)
Ceritified	AHRI ALICE CERTIFIED. September 19920 September 19920
	UL CUL US ENERGY STAR
	LISTED



Dawar aunnlu	E DATA	
Power supply	0.4.51.11.	000/000/4/5/ 00/
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60H
Voltage Range	(V)	187-25
Electrical		
Minimum circuit ampacity	(A)	30.8
Max.fuse	(A)	40.0
Connection wiring		14AWG*4 Stranded, unshielde
Cooling		
Capacity	(Btu/h)	27000(8000~3200
Power Input	`(W) [′]	2280(860~364
Current	(A)	10.0(3.75~1
SEER2	(Btu/W)	` 19.
EER2	(Btu/W)	11.
Heating	,	
Capacity	(Btu/h)	27000(12000~3600
Power Input	`(W) ´	2190(1257~355
Current	(A)	9.6(5.5~15.
HSPF2-4	(Btu/W)	10.
COP	W/W	3.6
Heat at 17F(H32)	(Btu/h)	2300
Heat at 5F(H42)	(Btu/h)	2700
	W/W	1.8

Outdoor(cooling)	(Deg. °F)	5~122
Outdoor(heating)	(Deg. °F)	-22~75

REFRIGERANT PIPE DATA		
Design pressure	(PSIG)	550/340
Refrigerant Type		R410A
Refrigerant charge	OZ	134.0
Refrigerant precharge	(ft)	25x3
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	3x1/4"
Gas side	(inch)	2x3/8"+1x1/2"
Max. length for all rooms	(ft)	196.9
Max. length for one indoor unit	(ft)	98.4
Max. height difference between indoor and outdoor unit	(ft)	49.2
Max. height difference between indoor units	(ft)	33.0

ROTARY KTF400D64UMTA GMCC 44390 3520 18.5 VG74/1000 ZKFN-120-8-2
KTF400D64UMTA GMCC 44390 3520 18.5 VG74/1000
GMCC 44390 3520 18.5 VG74/1000
44390 3520 18.5 VG74/1000
3520 18.5 VG74/1000
18.5 VG74/1000
VG74/1000
ZKFN-120-8-2 1
ZKFN-120-8-2 1
1
150.00
120.00
1.10
850/700/600
2147.06
62.00
37.24x16.14x31.89
42.91x19.69x34.84
164.90/177.47

