## SUBMITTAL DATA SHEET



Multi Zone Heat Pump			
Approval:			
Date:			
Construction:			
Unit #:			
Drawing #:			
	Approval: Date: Construction: Unit #: Drawing #:		

Outdoor unit code	22022316001865
Outdoor unit model	BMM27HH2C (Non-Ducted)
Ceritified	AHRI GERTIFED.  SERVICE STREET
	UL CUL US ENERGY STAR
	LISTED



SYSTEM PERFORMANCE DATA		
Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60H
Voltage Range	(V)	187-25
Electrical		
Minimum circuit ampacity	(A)	30.5
Max.fuse	(A)	40.0
Connection wiring		14AWG*4 Stranded, unshielder
Cooling		
Capacity	(Btu/h)	27000(10500~34000
Power Input	(W)	2287(822~3500
Current	(A)	9.95(3.6~15.3
SEER2	(Btu/W)	20.5
EER2	(Btu/W)	11.8
Heating		
Capacity	(Btu/h)	27000(9800~36000
Power Input	(W)	2241(697~3450
Current	(A)	9.75(3.2~15
HSPF2-4	(Btu/W)	9.6
COP	W/W	3.53
Heat at 17F(H32)	(Btu/h)	22500
Heat at 5F(H42)	(Btu/h)	27000
COP at 5F(H42)	`w/w <sup>′</sup>	1.80

Outdoor(cooling)	(Deg. °F)	5~122
Outdoor(heating)	(Deg. °F)	-22~75

Design pressure	(PSIG)	550/340
Refrigerant Type		R410A
Refrigerant charge	OZ	134.0
Refrigerant precharge	(ft)	25x3
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	3x1/4"
Gas side	(inch)	2x3/8"+1x1/2"
Max. length for all rooms	(ft)	196.9
Max. length for one indoor unit	(ft)	98.4
Max. height difference between indoor and outdoor unit	(ft)	49.2
Max. height difference between indoor units	(ft)	33.0

OUTDOOR UNIT DATA		
Compressor		
Туре		ROTARY
Model		KTF400D64UMTA
Brand		GMCC
Capacity	(Btu/h)	44390
Input	(W)	3520
Rated current (RLA)	(A)	18.5
Refrigerant oil/oil charge	(ml)	VG74/1000
Outdoor fan motor		
Model		ZKFN-120-8-2
Qty		1
Input	(W)	150.00
Output	(W)	120.00
RLA	(A)	1.10
Speed	(r/min)	850/700/600
Air flow & Noise level		
Outdoor air flow (Max.)	(CFM)	2147.06
Outdoor noise level	[dB(A)]	62.00
Outdoor unit		
Dimension (W×D×H)	(inch)	37.24x16.14x31.89
Packing (W×D×H)	(inch)	42.91x19.69x34.84
Net/ Gross weight	(lbs.)	164.90/177.47

