## SUBMITTAL DATA SHEET



Multi Zone Heat Pump			
	Approval:		
Location:			
Engineer:	Construction:		
Submitted to:	Unit #:		
Toubilitted by.	Diawing #.		
Reference:			



SYSTEM PERFORMANCE Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60Hz
Voltage Range	(V, F11, 112) (V)	187-253
Voltage Harige	( • )	107 250
Electrical		
Minimum circuit ampacity	(A)	25.0
Max.fuse	(A)	40.0
Connection wiring	, ,	14AWG*4 Stranded, unshielded
Cooling		
Capacity	(Btu/h)	26000/0700 40200
Power Input	(Btu/II) (W)	36000(8789~40288) 3273(354~4236)
Current	(VV) (A)	14.8(5.31~18.68)
SEER2	(Btu/W)	14.0(5.51~16.06)
EER2	(Btu/W)	20.0
Heating	(Dtd/VV)	11.0
Capacity	(Btu/h)	37000(6900~46624)
Power Input	(W)	2962(504~4307)
Current	(A)	13.0(5.76~19.07)
HSPF2-4	(Btu/W)	13.0(3.76~19.07)
COP	` ,	
Heat at 17F(H32)	W/W	3.66
Heat at 5F(H42)	(Btu/h)	27400
COP at 5F(H42)	(Btu/h)	24000
	W/W	1.68

Outdoor(cooling)	(Deg. °F)	5~122
Outdoor(heating)	(Deg. °F)	-13~75

Design pressure	(PSIG)	550/340
Refrigerant Type	,	R410A
Refrigerant charge	OZ	134.0
Refrigerant precharge	(ft)	25x4
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	4x1/4'
Gas side	(inch)	3x3/8"+1x1/2"
Max. length for all rooms	(ft)	262.5
Max. length for one indoor unit	(ft)	114.8
Max. height difference between indoor and outdoor unit	(ft)	49.2
Max. height difference between indoor units	(ft)	33.0

OUTDOOR UNIT DATA		
Compressor		
Туре		ROTARY
Model		KTF310D43UMT
Brand		GMCC
Capacity	(Btu/h)	34154
Input	(W)	2765
Rated current (RLA)	(A)	18
Refrigerant oil/oil charge	(ml)	VG74/1000
Outdoor fan motor		
Model		ZKFN-120-8-2
Qty		1
Input	(W)	150.0
Output	(W)	120.0
RLA	(A)	1.0
Speed	(r/min)	1000/900/750
Air flow & Noise level		
Outdoor air flow (Max.)	(CFM)	2147.06
Outdoor noise level	[dB(A)]	62.50
Outdoor unit		
Dimension (W×D×H)	(inch)	37.24x16.14x31.89
Packing (W×D×H)	(inch)	42.91x19.69x34.84
Net/ Gross weight	(lbs.)	169.09/ 76.7/82.3

