## SUBMITTAL DATA SHEET



Approval:
Date:
Construction:
Unit #:
Drawing #:

Outdoor unit code

22022316001945

Outdoor unit model

BMM36HH2C (Ducted)

Ceritified

AHRI

UL

CULUS

ENERGY STAR



Dower cumply		
Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60Hz
Voltage Range	(V)	187-253
Electrical		
Minimum circuit ampacity	(A)	36
Max.fuse	(A)	50
Connection wiring		14AWG*4 Stranded, unshielded
Cooling		
Capacity	(Btu/h)	36000(12000~40000)
Power Input	(W)	3000(800~4440)
Current	(A)	13.4(3.7~19.7)
SEER2	(Btu/W)	19.4
EER2	(Btu/W)	12.0
Heating		
Capacity	(Btu/h)	36000(12000~46000)
Power Input	(W)	3070(850~4330)
Current	(A)	13.6(3.7~19.1)
HSPF2-4	(Btu/W)	10.0
COP	W/W	3.44
Heat at 17F(H32)	(Btu/h)	30000
Heat at 5F(H42)	(Btu/h)	36000
COP at 5F(H42)	W/W	1.9

Outdoor(cooling)	(Deg. °F)	(-22)~122
Outdoor(heating)	(Deg. °F)	-22~75

REFRIGERANT PIPE DATA		
Design pressure	(PSIG)	550/340
Refrigerant Type		R410A
Refrigerant charge	OZ	148.0
Refrigerant precharge	(ft)	25x4
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Ф9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	4x1/4"
Gas side	(inch)	2x3/8"+2x1/2"
Max. length for all rooms	(ft)	262.46
Max. length for one indoor unit	(ft)	114.83
Max. height difference between indoor and outdoor unit	(ft)	49.21
Max. height difference between indoor units	(ft)	33.0

OUTDOOR UNIT DATA		
Compressor		
Туре		ROTARY
Model		EAPQ420D1UMUA
Brand		GMCC
Capacity	(Btu/h)	44015
Input	(W)	3565
Rated current (RLA)	(A)	21.5
Refrigerant oil/oil charge	(ml)	1460±15mlESTER OIL VG74
Outdoor fan motor		
Model		ZKFN-250-10-1
Qty		1
Input	(W)	1
Output	(W)	250.00
RLA	(A)	1.5
Speed	(r/min)	750/700/650
Air flow & Noise level		
Outdoor air flow (Max.)	(CFM)	3035.29
Outdoor noise level	[dB(A)]	65
Outdoor unit		
Dimension (W×D×H)	(inch)	38.58x16.34x38.39
Packing (W×D×H)	(inch)	45.08x19.69x42.52
Net/ Gross weight	(lbs.)	213.85/246.92

