SUBMITTAL DATA SHEET



Multi Zone Heat Pump				
Approval:				
Date:				
Construction:				
Unit #:				
Drawing #:				

Outdoor unit code

22022316001165

Outdoor unit model

BMM48HHC Ducted

Ceritified

AHRI


UL

CUL US

ENERGY STAR



Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60H;
Voltage Range	(V)	187-253
Electrical		
Minimum circuit ampacity	(A)	40.0
Max.fuse	(A)	60.0
Connection wiring		14AWG*4 Stranded, unshielded
Cooling		
Capacity	(Btu/h)	47000(18500~51000
Powrer Input	(W)	4020(750~4820
Current	(A)	18.2(5.8~21.2
SEER2	(Btu/W)	20.9
EER2	(Btu/W)	11.7
Heating		
Capacity	(Btu/h)	49000(12000~59000
Powrer Input	(W)	3900(710~5370
Current	(A)	17.2(5.7~23.8
HSPF2-4	(Btu/W)	8.9
COP	W/W	3.68
Heat at 17F(H32)	(Btu/h)	36000
Heat at 5F(H42)	(Btu/h)	42500
COP at 5F(H42)	W/W	2.00



REFRIGERANT PIPE DATA		
Design pressure	(PSIG)	550/340
Refrigerant Type		R410A
Refrigerant charge	OZ	162.0
Refrigerant precharge	(ft)	25x5
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	5x1/4"
Gas side	(inch)	3x3/8"+2x1/2"
Max. length for all rooms	(ft)	262.5
Max. length for one indoor unit	(ft)	114.8
Max. height difference between indoor and outdoor unit	(ft)	49.2
Max. height difference between indoor units	(ft)	33.0

OUTDOOR UNIT DATA		
Compressor		
Type		ROTARY
Model		EAPQ420D1UMUA
Brand		EAPQ420D TOMOA GMCC
1	(Dt. /l-)	
Capacity	(Btu/h)	44015
Input	(W)	3565
Rated current (RLA)	(A)	30
Refrigerant oil/oil charge	(ml)	1460±15mlESTER OIL VG74
Outdoor fan motor		
Model		ZKFN-85-8-22-5
Qty		2
Input	(W)	126.00
Output	(W)	85.00
RLA	(A)	1.00
Speed	(r/min)	900/850/800/750
Air flow & Noise level	(, ,	
Outdoor air flow (Max.)	(CFM)	4500.00
Outdoor noise level	[dB(A)]	65.00
Outdoor unit		
Dimension (W×D×H)	(inch)	37.48x16.34x52.48
Packing (W×D×H)	(inch)	43.11x19.49x58.27
Net/ Gross weight	(lbs.)	238.32/269.84

