## SUBMITTAL DATA SHEET



Approval:
Date:
Construction:
Unit #:
Drawing #:



01012m1 210 010m 1102	DATA	
Power supply		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60Hz
Voltage Range	(V)	187-253
Electrical		
Minimum circuit ampacity	(A)	40.0
Max.fuse	(A)	60.0
Connection wiring		14AWG*4 Stranded, unshielded
Cooling		
Capacity	(Btu/h)	55000(19400~57100)
Power Input	(W)	5238(600~6050)
Current	(A)	23.5(3.7~27.2)
SEER2	(Btu/W)	19.0
EER2	(Btu/W)	10.5
Heating		
Capacity	(Btu/h)	55000(15500~61600)
Powrer Input	(W)	4884(940~5600)
Current	(A)	21.5(4.9~26)
HSPF2-4	(Btu/W)	8.6
COP	W/W	3.30
Heat at 17F(H32)	(Btu/h)	35200
Heat at 5F(H42)	(Btu/h)	33200
COP at 5F(H42)	`w/w´	1.70

Outdoor(cooling)	(Deg. °F)	5~122
Outdoor(heating)	(Deg. °F)	-13~75

REFRIGERANT PIPE DATA		
Design pressure	(PSIG)	550/340
Refrigerant Type		R410A
Refrigerant charge	OZ	162.0
Refrigerant precharge	(ft)	25x5
Additional charge for each ft (Φ6. 35 (1/4") liquid pipe)	(oz/ft)	0.16
Additional charge for each ft (Φ9. 52 (3/8") liquid pipe)	(oz/ft)	0.32
Liquid side	(inch)	5x1/4"
Gas side	(inch)	3x3/8"+2x1/2"
Max. length for all rooms	(ft)	262.5
Max. length for one indoor unit	(ft)	114.8
Max. height difference between indoor and outdoor unit	(ft)	49.2
Max. height difference between indoor units	(ft)	33.0

Compressor		
Туре		ROTAR'
Model		KTQ420D1UMU
Brand		GMCC
Capacity	(Btu/h)	4674
Input	(W)	370
Rated current (RLA)	(A)	25.
Refrigerant oil/oil charge	(ml)	VG74/140
Outdoor fan motor		
Model		ZKFN-85-8-22-
Qty		2
Input	(W)	126.0
Output	(W)	85.0
RLA	(A)	2.5
Speed	(r/min)	900/850/800/75
Air flow & Noise level		
Outdoor air flow (Max.)	(CFM)	4500.00
Outdoor noise level	[dB(A)]	62.00
Outdoor unit		
Dimension (W×D×H)	(inch)	37.48x16.34x52.4
Packing (W×D×H)	(inch)	43.11x19.49x58.2
	(lbs.)	224.21/257.2

