

SUBMITTAL DATA SHEET

Inverter Ducted Heat Pump System

Location:

Approval:

Engineer:

Date:

Submitted to:

Construction:

Submitted by:

Unit #:

Reference:

Drawing #:

SYSTEM INFORMATION

System Model		BNG2Z60SCN-48DH
Cooling Capacity	BTU/hr	54000
Heating Capacity	BTU/hr	54000
SEER2		19
HSPF2		9.5
EER2	(BTU/h)/W	11.7
COP	W/W	3.4

OUTDOOR UNIT SPECIFICATION

Model Number		BNG2Z60SCN
Compressor Type		Inverter Rotary
Compressor RLA	A	30.1
Fan Type		Axial-flow
Fan Quantity		2
Fan Motor Output		2×1/6 HP
Airflow	CFM	4000
Sound Pressure Level	dBA	63
Dimension (W × D × H)	inch	35.44 × 13.38 × 49.63
Net/Gross Weight	lbs	214.0 / 236.0

AIR HANDLER SPECIFICATION

Model Number		BNG2Z48DH0
Unit Type		Multi-Position Air Handler
Fan Type		Centrifugal
Fan Motor Output		1 HP
Fan Motor FLA	A	5.50
Airflow	CFM	1200
External Static Pressure	inWG	0.5
Static Pressure Range	inWG	0-1
Sound Pressure Level	dBA	52
Electric Heater Options	W	6000/9000/12000 W
Dimension (W × D × H)	inch	24.80 × 21.26 × 51.97

Net/Gross Weight	lbs	199.5 / 218.3
------------------	-----	---------------

ELECTRICAL		
Power Supply	208-230V / 1Ph / 60Hz	
Cooling Power Input	4.62 kW	
Heating Power Input	4.66 kW	
Cooling Current	21.1 A	
Heating Current	21.3 A	
MCA (Min. Circuit Ampacity)	35.5 A	
Max. Over Current Protection	40 A	

REFRIGERANT		
Refrigerant Type	R32	
Refrigerant Charge	148.2 oz	
GWP	675	

OPERATING CONDITIONS		
Cooling Ambient Temperature Range	5°F to 118°F (-15°C to 48°C)	
Heating Ambient Temperature Range	5°F to 75°F (-15°C to 24°C)	

PIPING / LINE SET		
Liquid Line (OD)	3/8"	
Gas/Suction Line (OD)	3/4"	
Pre-Charged Line Set Length	24.6 ft	
Max. Line Set Length	98.4 ft	
Max. Height Difference	49.2 ft	
Additional Refrigerant Charge	0.215 oz/ft	

RLA: Rated Load Amps | FLA: Full Load Amps | MCA: Minimum Circuit Ampacity | GWP: Global Warming Potential

AHRI Certified | ETL Listed

Model: BNG2Z60SCN-48DH