

SUBMITTAL DATA SHEET

Multi-Position Air Handler

Location: Approval:
Engineer: Date:
Submitted to: Construction:
Submitted by: Unit #:
Reference: Drawing #:

UNIT SPECIFICATION

Model Number		BNGFZ60DH0
Series		Flexx
Unit Type		Multi-Position Air Handler
Airflow	CFM	1500
External Static Pressure	inWG	0.5
Static Pressure Range	inWG	0-1
Sound Pressure Level	dBA	53
Sound Power Level	dBA	63

FAN / MOTOR

Fan Type		Centrifugal
Fan Quantity		1
Motor Output		1 HP
Motor FLA	A	6.00
Motor Speed		1000 rpm
Drive Type		Direct-driven

ELECTRICAL

Power Supply		208-230V / 1Ph / 60Hz
Voltage Range		187-253 V
Cooling Power Input		0.42 kW
Heating Power Input		0.37 kW
Cooling Current		2.80 A
Heating Current		2.50 A
Circuit Breaker		15 A
Max. Over Current Protection		15 A
Electric Heater Options		6000/9000/12000 W

EVAPORATOR COIL

Refrigerant		R32
Number of Rows		4
Fins per Inch (FPI)		14

FILTER / DRAIN	
Filter Type	Metal
Filter Size	23.0" × 20.3"
Drain Connection	1"

DIMENSIONS	
Dimension (W × D × H)	24.80" × 21.26" × 51.97"
Net Weight	199.5 lbs
Gross Weight	218.3 lbs

RLA: Rated Load Amps | FLA: Full Load Amps | MCA: Minimum Circuit Ampacity | GWP: Global Warming Potential

AHRI Certified | ETL Listed

Model: BNGFZ60DH0