

# SUBMITTAL DATA SHEET

Model: BXAFA09CDH

## Concealed Duct Indoor Unit

Location:		Approval:	
Engineer:		Date:	
Submitted to:		Construction:	
Submitted by:		Unit #:	
Reference:		Drawing #:	

## INDOOR UNIT SPECIFICATION

Model Number		BXAFA09CDH
Cooling Capacity	BTU/hr	9,000
Heating Capacity	BTU/hr	9,900
Air Flow (Turbo/Hi/Mi/Lo/Si)	CFM	344 / 288 / 231 / 201 / 122
Indoor Noise Level (Hi/Mi/Lo/Si)	dBA	29.5 / 28.5 / 27.5 / 26
Static Pressure Range	in.w.g.	0 - 0.8
Fan Motor Output	W	165
Fan Motor RLA	A	1.5
Dimension (W × D × H)	inch	27.56 × 29.53 × 9.65
Net/Gross Weight	lbs	64.15 / 73.85

## ELECTRICAL

Power Supply		208-230V / 1Ph / 60Hz
Connection Wiring		14# × 4

## PIPING

<b>Liquid Pipe Size</b>		1/4"
<b>Gas Pipe Size</b>		3/8"

RLA: Rated Load Amps | MCA: Minimum Circuit Ampacity | Compatible with BXS5A09UC0 outdoor unit  
AHR1 Certified | ETL Listed | Refrigerant Type: R454B

Model: BXAFA12CDH