

SUBMITTAL DATA SHEET

Model: BXAFA18CDH

Concealed Duct Indoor Unit

Location:		Approval:	
Engineer:		Date:	
Submitted to:		Construction:	
Submitted by:		Unit #:	
Reference:		Drawing #:	

INDOOR UNIT SPECIFICATION

Model Number		BXAFA18CDH
Cooling Capacity	BTU/hr	17,500
Heating Capacity	BTU/hr	19,500
Air Flow (Turbo/Hi/Mi/Lo)	CFM	706 / 618 / 530 / 441
Indoor Noise Level (Hi/Mi/Lo/Si)	dBA	36 / 34 / 32 / 28
Static Pressure Range	in.w.g.	0 - 0.8
Fan Motor Output	W	165
Fan Motor RLA	A	1.8
Dimension (W × D × H)	inch	39.37 × 29.53 × 9.65
Net/Gross Weight	lbs	79.81 / 91.27

ELECTRICAL

Power Supply		208-230V / 1Ph / 60Hz
Connection Wiring		14# × 4

PIPING

Liquid Pipe Size		1/4"
Gas Pipe Size		1/2"
RLA: Rated Load Amps MCA: Minimum Circuit Ampacity Compatible with BXS5A18UC0 outdoor unit AHRI Certified ETL Listed Refrigerant Type: R454B		