

SUBMITTAL DATA SHEET

Model: BXAFA24CDH

Concealed Duct Indoor Unit

Location:		Approval:	
Engineer:		Date:	
Submitted to:		Construction:	
Submitted by:		Unit #:	
Reference:		Drawing #:	

INDOOR UNIT SPECIFICATION

Model Number		BXAFA24CDH
Cooling Capacity	BTU/hr	24,000
Heating Capacity	BTU/hr	26,000
Air Flow (Turbo/Hi/Mi/Lo)	CFM	854 / 706 / 618 / 500
Indoor Noise Level (Hi/Mi/Lo/Si)	dBA	40 / 37 / 35 / 29.5
Static Pressure Range	in.w.g.	0 - 0.8
Fan Motor Output	W	165
Fan Motor RLA	A	2.2
Dimension (W × D × H)	inch	39.37 × 29.53 × 9.65
Net/Gross Weight	lbs	80.47 / 91.93

ELECTRICAL

Power Supply		208-230V / 1Ph / 60Hz
Connection Wiring		14# × 4

PIPING

Liquid Pipe Size		3/8"
Gas Pipe Size		5/8"

RLA: Rated Load Amps | MCA: Minimum Circuit Ampacity | Compatible with BXS5A24UC0 outdoor unit
AHRI Certified | ETL Listed | Refrigerant Type: R454B