

# SUBMITTAL DATA SHEET

Model: BXAFZ24CDH

## Slim Duct Air Handler

<b>Location:</b>		<b>Approval:</b>	
<b>Engineer:</b>		<b>Date:</b>	
<b>Submitted to:</b>		<b>Construction:</b>	
<b>Submitted by:</b>		<b>Unit #:</b>	
<b>Reference:</b>		<b>Drawing #:</b>	

## AIR HANDLER SPECIFICATION

<b>Model Number</b>		BXAFZ24CDH
<b>Capacity</b>	BTU/hr	24,000
<b>Indoor Air Flow (Turbo/H/M/L/Si)</b>	CFM	1030 / 824 / 736 / 577
<b>Indoor Noise Level (Turbo/H/M/L/Si)</b>	dBa	41 / 32 / 30 / 27
<b>Dimension (W × D × H)</b>	inch	44.5 × 29.7 × 11.8
<b>Package (W × D × H)</b>	inch	47.3 × 31.9 × 13.6
<b>Net/Gross Weight</b>	lbs	92.6
<b>Supply Air Opening (A × B × C)</b>	inch	7-5/8 × 29-9/16 × 1
<b>Return Air Opening (D × E × F)</b>	inch	10-3/8 × 37-3/4 × 1-1/8

## ELECTRICAL

<b>Indoor Fan Motor RLA</b>		N/A
<b>Indoor Fan Motor</b>	W	200

## PIPING

<b>Liquid Size</b>		1/4"
<b>Gas Size</b>		5/8"
<b>Connection Method</b>		Flared

RLA: Rated load amps (A) | W: Fan motor rated output (W)

AHRI Certified | ETL Listed