

# SUBMITTAL DATA SHEET

Model: BXS4Z09UCO - Series XS4

## Outdoor Condensing Unit

Location:		Approval:	
Engineer:		Date:	
Submitted to:		Construction:	
Submitted by:		Unit #:	
Reference:		Drawing #:	

## OUTDOOR UNIT SPECIFICATION

Model Number	BXS4Z09UCO	
Capacity	BTU/hr	9000
Compressor Type	Inverter Rotary	
Compressor Model	QXF-B103zH170E	
Refrigerant	R-32	
Refrigerant Oil	RB68EP	
Outdoor Air Flow (Max)	CFM	1295
Outdoor Noise Level	dBA	52
Dimension (W x D x H)	inch	31.58 x 21.84 x 13.78
Package (W x D x H)	inch	34.22 x 15.55 x 23.39
Net/Gross Weight	lbs	70.6 / 76.1

## EFFICIENCY

SEER2	Varies by indoor unit combination
EER2	Varies by indoor unit combination
HSPF2	Varies by indoor unit combination
COP	Varies by indoor unit combination

## ELECTRICAL

Power Supply	208/230V, 60Hz, 1Ph
System MCA	10
System MOCP (Max Breaker)	15
Compressor RLA	6.5
Outdoor Fan Motor RLA	0.96
Outdoor Fan Motor W	30

## PIPING

<b>Throttle type(Outdoor)</b>	Electron expansion valve
<b>Liquid Size</b>	1/4"
<b>Gas Size</b>	3/8"
<b>Max. Piping Length(ft/m)</b>	65
<b>Max. Height Difference(ft/m)</b>	40
<b>Max. Pre-charged Length(ft/m)</b>	24.6
<b>Refrigerant Pre-charged Amount(oz)</b>	30
<b>Additional Charge of Refrigerant(oz/ft)</b>	0.2
<b>Connection Method</b>	Flare

MCA: Min. circuit amps (A) | MOCP: Max. over current protection (A)

RLA: Rated load amps (A) | W: Fan motor rated output (W)

AHRI Certified | ETL Listed