

SUBMITTAL DATA SHEET

Model: BXS4Z09UCV - Series XS4

Outdoor Condensing Unit

Location:		Approval:	
Engineer:		Date:	
Submitted to:		Construction:	
Submitted by:		Unit #:	
Reference:		Drawing #:	

OUTDOOR UNIT SPECIFICATION

Model Number	BXS4Z09UCV	
Capacity	BTU/hr	9000
Compressor Type	Inverter Rotary	
Compressor Model	QXF-B103zH170E	
Refrigerant	R-32	
Refrigerant Oil	RB68EP	
Outdoor Air Flow (Max)	CFM	1295
Outdoor Noise Level	dBA	52
Dimension (W x D x H)	inch	31.58 x 21.84 x 13.78
Package (W x D x H)	inch	34.22 x 15.55 x 23.39
Net/Gross Weight	lbs	71.7 / 77.2

EFFICIENCY

SEER2	27
EER2	15
HSPF2	10.5
COP	4

ELECTRICAL

Power Supply	115V, 60Hz, 1Ph
System MCA	19
System MOCP (Max Breaker)	20
Compressor RLA	13.5
Outdoor Fan Motor RLA	1.24
Outdoor Fan Motor W	30

PIPING	
Throttle type(Outdoor)	Electron expansion valve
Liquid Size	1/4"
Gas Size	3/8"
Max. Piping Length(ft/m)	65
Max. Height Difference(ft/m)	40
Max. Pre-charged Length(ft/m)	24.6
Refrigerant Pre-charged Amount(oz)	30
Additional Charge of Refrigerant(oz/ft)	0.2
Connection Method	Flare

MCA: Min. circuit amps (A) | MOCP: Max. over current protection (A)

RLA: Rated load amps (A) | W: Fan motor rated output (W)

AHRI Certified | ETL Listed