

ITEM # FTXM12WVJU9, FTXM-V SERIES

- Wall Mounted unit using R-32 Refrigerant (may not be available in your area - check local codes regarding sale and installation).
- Built-in Wi-Fi to control the system with the Daikin Comfort Control App
- Hybrid Cooling technology controls humidity efficiently even in low cooling loads and maintains dehumidification effect after the target temperature is reached.
- CLEAN function dries the interior of the indoor unit to reduce the amount of condensation present.
- The indoor unit has been re-

[+ more](#)



[Specifications](#) | [Electrical Data](#) | [Dimensions](#)

Specifications

| | |
|---|----------------------------|
| Rated Capacity (Min. - Max.) - Cooling | 12000 (4800 - 16000) Btu/h |
| Rated Capacity (Min. - Max.) - Heating | 13600 (4800 - 22600) Btu/h |
| Power Consumption Rated - Cooling | 909 W |
| Power Consumption Rated - Heating | 906 W |
| Power Factor - Cooling | 96.3 - 96.2 % |
| Power Factor - Heating | 96.8 - 96.8 % |
| SEER2 / HSPF2 - Cooling | 25.20 |
| SEER2 / HSPF2 - Heating | 10.70 |
| EER2 Rated | 13.20 Btu/h-W |
| COP2 Rated | 4.40 W/W |

| | |
|--|--|
| Amount of Additional Charge of Refrigerant | 0.22 oz/ft 20 g/m |
| Front Panel Color | White (N-9.5) |
| Airflow Rate (H) - Cooling | 558 ft ³ /min 15.8 m ³ /min |
| Airflow Rate (H) - Heating | 558 ft ³ /min 15.8 m ³ /min |
| Airflow Rate (M) - Cooling | 395 ft ³ /min 11.2 m ³ /min |
| Airflow Rate (M) - Heating | 413 ft ³ /min 11.7 m ³ /min |
| Airflow Rate (L) - Cooling | 293 ft ³ /min 8.3 m ³ /min |
| Airflow Rate (L) - Heating | 339 ft ³ /min 9.6 m ³ /min |
| Airflow Rate (SL) - Cooling | 226 ft ³ /min 6.4 m ³ /min |
| Airflow Rate (SL) - Heating | 254 ft ³ /min 7.2 m ³ /min |
| Fan Type | Cross Flow Fan |
| Fan Speed | 5 Steps, Quiet, Auto |
| Heat Exchanger Type | Multi Slit Fin |
| Heat Exchanger - Rows x Stages | 1 × 4 1 × 8 2 × 18 |
| Heat Exchanger - Fin per Inch | 18 |
| Sound Pressure Level (H) - Cooling | 45 dBA |
| Sound Pressure Level (H) - Heating | 45 dBA |
| Sound Pressure Level (M) - Cooling | 37 dBA |
| Sound Pressure Level (M) - Heating | 39 dBA |
| Sound Pressure Level (L) - Cooling | 29 dBA |

| | |
|------------------------------------|--------|
| Sound Pressure Level (L) - Heating | 32 dBA |
|------------------------------------|--------|

| | |
|-------------------------------------|--------|
| Sound Pressure Level (SL) - Cooling | 23 dBA |
|-------------------------------------|--------|

| | |
|-------------------------------------|--------|
| Sound Pressure Level (SL) - Heating | 26 dBA |
|-------------------------------------|--------|

| | |
|--------|-------|
| Weight | 29 lb |
| | 13 kg |

| | |
|--------------|-------|
| Gross Weight | 38 lb |
| | 17 kg |

Electrical Data

| | |
|---------|--------------|
| Voltage | 208 to 230 V |
|---------|--------------|

| | |
|-----------|-------|
| Frequency | 60 Hz |
|-----------|-------|

| | |
|------------------|---|
| Number of Phases | 1 |
|------------------|---|

| | |
|-----------------------|--------|
| Min. Circuit Ampacity | 12.3 A |
|-----------------------|--------|

| | |
|--------------------|------|
| Max. Fuse Ampacity | 15 A |
|--------------------|------|

| | |
|-----------------|---------|
| Rated Load Amps | 12.00 A |
|-----------------|---------|

| | |
|----------------------------------|---------|
| Outdoor Fan Motor - Rated Output | 0.05 hp |
| | 37 W |

| | |
|------------------------------------|--------|
| Outdoor Fan Motor - Full Load Amps | 0.31 A |
|------------------------------------|--------|

| | |
|---------------------------------|---------|
| Indoor Fan Motor - Rated Output | 0.04 hp |
| | 27 W |

| | |
|-----------------------------------|--------|
| Indoor Fan Motor - Full Load Amps | 0.25 A |
|-----------------------------------|--------|

Dimensions

| | |
|-------|-------------|
| Depth | 10-13/16 in |
| | 275 mm |

| | |
|-------|-----------|
| Width | 36-1/4 in |
| | 920 mm |

| | |
|--------|-----------|
| Height | 11-3/4 in |
| | 299 mm |

| | |
|-----------------------|---------------------|
| Packaged Depth | 15-3/8 in 391 mm |
|-----------------------|---------------------|

| | |
|-----------------------|----------------------|
| Packaged Width | 39-3/4 in 1010 mm |
|-----------------------|----------------------|

| | |
|------------------------|-----------------------|
| Packaged Height | 14-15/16 in 380 mm |
|------------------------|-----------------------|

| | |
|----------------------------------|------------------|
| Pipe Connections - Liquid | 1/4 in 6.4 mm |
|----------------------------------|------------------|

| | |
|-------------------------------|------------------|
| Pipe Connections - Gas | 3/8 in 9.5 mm |
|-------------------------------|------------------|

| | |
|---------------------------------|-------------------|
| Pipe Connections - Drain | 5/8 in 16.0 mm |
|---------------------------------|-------------------|

| | |
|-------------------------------------|--------------------|
| Max. Interunit Piping Length | 82-1/64 in 25 m |
|-------------------------------------|--------------------|

| | |
|---|-------------------|
| Max. Interunit Height Difference | 65-5/8 in 20 m |
|---|-------------------|

| | |
|-------------------|-----------------|
| Chargeless | 49.2 in 15 m |
|-------------------|-----------------|