

COOLING PERFORMANCE DATA																						
Model	Cooling																					
	Indoor Conditions DB		-22F	-13F	-4F	0F	5F	17F	35F	35F	47F	55F	65F	75F	80F	85F	95F	105F	110F	115F	122F	
			-30°C	-25°C	-20°C	-17.8°C	-15°C	-8.3°C	1.7°C	1.7°C	8.3°C	12.8°C	18.3°C	24°C	26.7°C	29.4°C	35°C	40.5°C	43.3°C	46°C	50°C	
BMY9HH28C+BM09MCC	65 F (18.3°C)	TC	8010	8710	8860	9170	9140	9140	9380	9580	10260	10670	10750	11190	11380	10770	10310	10050	9130	8620	7720	
		SC	4900	5610	5930	6270	6270	6410	6910	7160	7520	8240	8280	8810	8870	8700	8610	8670	8280	8160	7710	
		Input	310	360	390	440	440	500	550	600	650	690	730	740	810	910	1140	1150	1100	1150	1170	
	70 F (21.1°C)	TC	8420	9160	9410	9560	9670	9670	9860	10040	10870	11150	11430	11860	11860	11280	10790	10540	9640	9110	8070	
		SC	5130	5860	6270	6510	6600	6750	7230	7470	7920	8570	8760	9280	9190	9070	8950	9030	8690	8580	8030	
		Input	310	360	390	430	450	510	550	590	650	690	740	750	790	920	1140	1140	1100	1160	1170	
	75 F (23.9°C)	TC	8930	9590	9920	9980	10280	10230	10410	10480	11320	11850	11930	12400	12470	11950	11400	10970	10250	9620	8410	
		SC	5400	6110	6570	6750	6980	7110	7590	7750	8200	9050	9090	9670	9600	9550	9410	9360	9200	9000	8330	
		Input	310	360	400	420	450	510	550	590	650	700	720	750	790	930	1140	1140	1120	1160	1160	
	80 F (26.7°C)	TC	9320	10020	10440	10620	10760	10890	10930	10970	12040	12350	12660	12960	13240	12690	12120	11550	10900	10070	8900	
		SC	5610	6340	6880	7140	7270	7520	7940	8080	8670	9390	9580	10040	10130	10090	9940	9800	9730	9380	8770	
		Input	310	360	400	420	450	520	550	590	660	690	720	760	790	1080	1150	1140	1130	1140	1150	
	BMY12HH26+BM12MCC	65 F (18.3°C)	TC	9600	10480	10680	10980	11170	11100	11370	11160	10890	10870	11080	11190	11130	11390	11770	11110	10520	9910	8700
			SC	5820	6820	7170	7310	7520	8030	8420	8050	7880	8200	8580	8690	8680	9000	9400	9280	9500	9240	8640
			Input	390	470	500	530	570	630	640	660	660	670	700	710	720	900	1320	1280	1280	1320	1320
70 F (21.1°C)		TC	10190	10950	11200	11530	11740	11790	11860	11750	11480	11530	11580	11730	11740	12050	12360	11650	11170	10400	9070	
		SC	6150	7090	7480	7640	7860	8500	8730	8420	8260	8660	8920	9060	9110	9470	9820	9670	10040	9640	8960	
		Input	390	460	500	540	570	630	640	650	660	670	700	710	710	910	1310	1280	1300	1310	1310	
75 F (23.9°C)		TC	10700	11430	11840	12180	12280	12380	12490	12330	12110	12100	12090	12300	12350	12770	13150	12310	11700	10880	9530	
		SC	6420	7360	7860	8020	8180	886														

